HOWO 6X4 12cmb foam tank fire fighting truck 12Tons EURO3 fire fighting truck for sale



Pr-Specification

Main specification							
Model and product name		JDF5280GXFSG120Z airport fire truck					
Gross weight (kg)		27600	Type of unit		6X4		
Payload (Kg)		12350			10025 × 2500 × 3600		
Empty weight (Kg)		14800	Cabin seats		6		
Approach / exit angle (°)		16/13	Front / rear drop (mm)		1500/2490		
Axis No.		3	Distance between axes (mm)		4600 + 1350		
Axle load (Kg)		6900/20700	Maximum speed (Km / 8		85	85	
Chassis specification							
Chassis model	ZZ1257M4647C		Maker			China SINOTRUK Group Jinan Truck Co., Ltd	
Name of the brand	SINOTRUK (HOWO)		Dimension (mm)			9895 × 2496 × 2958	
Specification of the tire	11.00-20		Tire			10	
Steel spring number	10/12		Front track base (mm)			2022	
Fuel type	Diesel		Rear track base (mm)			1830	
Issuance standard	Euro 3					10 forward, 2 reverse	
Cab	Four of struct	Four doors that open and the whole flat top with cabin of the crew, and all the welded structure of steel, hydraulic renewal mechanism with air conditioning					
Engine information	Engin	e model		WD615.97E			
		e manufacturer		China Heavy Duty Truck Group Co., Ltd			
	Displacement (ml) / Power (Kw) 9726/221						
	Max T	Corque		1250 N.m			
	Speed at maximum torque 2200 rpm						
Operation of water ta	nk fire	fighting truck					
Volume of the water tank (L)	12000 to 15000						
Fire Monitor	Fire monitor model PS50, rotation level in 360º, Maximum elevation + 45º, maximum depression angle -15º, Flow rate: 50L / S, Range≥60m / 1.0MPa						
Fire pump Model: CB10 / 60 Flow rate: 60L / S Pressure: 1.0MPa							
Feature of water tank							
			· · · · · · · · · · · · · · · · · · ·			1 1	

A. The water tank fire truck is mainly composed of the cabin, water tank, water pump house, equipment boxes, water pump, inlet and outlet water system, fire monitor, electronic alarm, alarm lamp, etc.B. The entire distribution of the truck is divided into three parts. The front is the passenger room. The central part

B. The entire distribution of the truck is divided into three parts. The front is the passenger room. The central part is the house of the pump. The back is the body of the truck. The front part of the body is the water tank, the back is the equipment. box.

C. It has the characteristic of high power, high speed and large liquid transport capacity, etc. The extended cab is adopted. With comfortable seating and centralized operation, simple maintenance,

D.it is widely used in the public safety fire brigade, the petroleum chemical industry, factories and mining companies and ports, terminals and other places to save the large amount of oil fire and general material fire in large cities and medium. It is the great ideal equipment against fires.

More Products

FACTORY OVERVIEW



Why choose us? 1. Q: How long is the warranty period? A: All of our trucks have one year warranty or 25000KM since you get the truck. 2. Q: What's the main market of your company? A: We have customers all over the world. And our main market it Africa.All the individuals and units are my partners who have a demand of china's high quality automobile industry product. 3. Q: How much the production capacity and supply capacity of your factory for one year? 4. A: This depends on your needs. 10 years of spare parts sales experience makes us have a smooth supply channels. 5. Q: Where is your factory located? A: Our company is located in Suizhou City, Hubei Province, the Capital of Special Purpose Vehicle in China.Warmly welcome to our factory. 6. Q: The reason why you chose our company? A: We have the abundant resources supply, professional quality inspection engineers, excellent service team, we will integrate all resources for your needs, let you experience the more cost-effective and more convenient "one-stop" procurement services, effectively reduce the purchasing cost.

Contact Us

